



American Fiber Cement Corporation

Installation Guidelines


INTERIOR

MAXIMUM
OCCUPANCY
43

Panel Joints


For interior applications, panel joints are not necessary but can be utilized to achieve a desired look. The diagrams below display the various panel joint options that can be used.

Open Joints



Open joints are not restricted to 3/8". Any dimension can be used. With this design, a black wrap is often put up behind the panels to make the open joints black.

Butt Joints



In interior applications, minimal temperature changes will prevent the panels from expanding and contracting. Therefore, it is ok to butt panel edges against one another.

*If the interior space is exposed to moisture and experiences large temperature fluctuations, the panels cannot butt together.

Lap Siding



Panels can also be installed as lap siding. Vertical joints can be left open or can butt together.

Screw Attachment

For interior applications, high-density fiber cement does not need to be installed in a ventilated rainscreen system. An airspace behind the fiber cement panels is not required. Weather barriers are also not required. Depending on the wall construction, American Fiber Cement Cladding can be installed in one of the following ways using screws (supplied by others) as the method of attachment.

1. Plywood Sheathing

- a. Sheathing thickness must be 1/2" or greater to fasten the panels directly to the sheathing
- b. Fasten panels directly to plywood sheathing
 - i. Stainless Steel Screws provided by AFCC or others
 - ii. Vertical rivet spacing 16"-24" o.c.
 - iii. Horizontal rivet spacing 16"-24" o.c.


2. Steel/Wood Studs with Interior Sheathing

- a. Fasten horizontal metal strapping spaced at 16"-24" o.c. into the studs
 - i. Metal strapping min. thickness is 18-gauge for steel and 1.5mm for aluminum
- b. Fasten panels onto horizontal strapping
 - i. Stainless Steel Screws provided by others
 - ii. Vertical screw spacing 16"-24" o.c.
 - iii. Horizontal screw spacing 16"-24" o.c.

3. Masonry Wall & Concrete Masonry Unit

- a. Fasten directly to masonry
- b. Use masonry screws provided by others

• Edge Distances Requirements



	mm	(in.)
h:	40–150	(1 ⁹ / ₁₆ –5 ⁷ / ₈)
v:	70–150	(2 ³ / ₄ –5 ⁷ / ₈)

• Additional Information

- No gliding points are required. The holes in panel can match the diameter of the fastener.
- Screws cannot be countersunk into panels.
- If the interior space is exposed to moisture and experiences large temperature fluctuations, the panels cannot butt together and gliding points will be required. Contact AFCC for more information.
- If the floor or grade level experiences moisture, keep grade line panels 2" off the floor to keep away from the moisture.

Hidden Attachment

For interior applications, high-density fiber cement does not need to be installed in a ventilated rainscreen system. An airspace behind the fiber cement panels is not required. Weather barriers are also not required. Depending on the wall construction, American Fiber Cement Cladding can be installed in one of the following ways using the *Dynamic Bond* hidden attachment system supplied by AFCC.

Note: Dynamic Bonding Systems installation instructions must be followed. For interior applications portions of the instructions do not need to be followed and are listed below. The Dynamic Bonding Systems installation instructions can be found at <http://www.americanfibercement.com/installation-instructions/>.

1. Plywood Sheathing

- a. Sheathing thickness must be 1/2" or greater to fasten the panels directly to the sheathing.
- b. Apply Dynamic Protect onto the plywood sheathing in horizontal or vertical rows spaced 16" on center or less. The Dynamic Protect must be applied where the Dynamic Bond glue bead strips will be run.
- c. Follow the Dynamic Bond Installation Instructions.
 - i. Dynamic Clean and Dynamic Tape must be used.
 - ii. Dynamic SI Epoxy does not need to be applied to the back of the fiber cement board for the Cover, Solid or Transparent but is required for Minerit HD and Patina product lines.

2. Steel/Wood Studs with Interior Sheathing

- a. Fasten horizontal metal strapping spaced at 16"-24" o.c. into the studs.
 - i. Metal strapping min. thickness is 18-gauge for steel and 1.5mm for aluminum
- b. Use Dynamic Bond to fasten the panels onto the horizontal strapping. Follow the Dynamic Bond Installation Instructions.
 - i. Dynamic Clean and Dynamic Tape must be used.
 - ii. Dynamic SI Epoxy does not need to be applied to the back of the fiber cement board for the Cover, Solid or Transparent but is required for Minerit HD and Patina product lines.

3. Masonry Wall

- a. Apply Dynamic SI Epoxy onto the Masonry wall in horizontal or vertical rows spaced 16" on center or less. The Dynamic SI Epoxy must be applied where the Dynamic Bond glue bead strips will be run.
- b. Follow the Dynamic Bond Installation Instructions.
 - i. Dynamic Clean and Dynamic Tape must be used.
 - ii. Dynamic SI Epoxy does not need to be applied to the back of the fiber cement board for the Cover, Solid or Transparent but is required for Minerit HD and Patina product lines.

4. Concrete Masonry Unit (CMU)

- a. Fasten vertical or horizontal metal strapping spaced at 16" o.c. into the CMU.
 - i. Metal strapping min. thickness is 18-gauge for steel and 1.5mm for aluminum
- b. Use Dynamic Bond to fasten the panels onto the horizontal strapping. Follow the Dynamic Bond Installation Instructions.
 - i. Dynamic Clean and Dynamic Tape must be used.
 - ii. Dynamic SI Epoxy does not need to be applied to the back of the fiber cement board for the Cover, Solid or Transparent but is required for Minerit HD and Patina product lines.

Limited Warranty

American Fiber Cement Corporation (AFCC) warrants that its products are manufactured in accordance with its applicable material specifications and are free from defects in materials and workmanship using AFCC's specifications as a standard. Only products which are installed and used in accordance with applicable AFCC instructions and specifications are in any way warranted by AFCC. This warranty is applicable only to claims made in writing and received by AFCC within thirty (30) days after the defect was discovered *and* within ten (10) years after the date of the shipment of the product by AFCC. All other claims are waived. If a claim is made, you must allow reasonable investigation of the product you claim is defective and you must supply samples that adequately demonstrate the problem you claim for testing by AFCC.

AFCC DISCLAIMS ALL IMPLIED WARRANTIES INCLUDING THE WARRANTY OF MERCHANTABILITY AND THE WARRANTY OF FITNESS FOR A PARTICULAR PURPOSE. THIS LIMITED WARRANTY PROVIDES YOUR EXCLUSIVE REMEDY AS A PURCHASER OF AFCC PRODUCTS. THIS LIMITED WARRANTY MAY BE MODIFIED OR AMENDED ONLY BY A WRITTEN INSTRUMENT SIGNED BY A DULY AUTHORIZED REPRESENTATIVE OF AFCC. WITHOUT AN EXPRESS, WRITTEN AUTHORIZATION FROM AFCC, NO RETAILER OR DISTRIBUTOR OF AFCC PRODUCTS HAS THE AUTHORITY TO MODIFY OR AMEND THIS LIMITED WARRANTY.

Limitation of Liability

This limited warranty is your sole and exclusive remedy. It is expressly understood and agreed that the limit of liability will be, at AFCC's option, repair, resupply of a like quantity of non-defective product, or refund of purchase price of the material. All labor and service charges which may be incurred with respect to either the original or replacement product are excluded. AFCC shall have no liability except where the claim results solely from breach of AFCC's limited warranty.

AFCC SHALL NOT BE LIABLE FOR ANY INCIDENTAL OR CONSEQUENTIAL DAMAGES. FURTHERMORE, AFCC SHALL NOT BE LIABLE FOR DAMAGE TO THE PROPERTY TO WHICH THE PRODUCT IS APPLIED OR ITS CONTENTS, LOSS OF TIME, PROFITS, OR ANY INCONVENIENCE ARISING OUT OF ANY BREACH OF THIS LIMITED WARRANTY OR OBLIGATIONS UNDER THIS LIMITED WARRANTY. AFCC SHALL NOT BE LIABLE FOR ANY DAMAGES WHICH ARE BASED UPON NEGLIGENCE, BREACH OF WARRANTY, STRICT LIABILITY, OR ANY OTHER THEORY EXCEPT THE LIMITED WARRANTY SET FORTH ABOVE. INCIDENTAL AND CONSEQUENTIAL DAMAGES SHALL NOT BE RECOVERABLE EVEN IF THE REPLACEMENT REMEDY FAILS OF ITS PURPOSE OR FOR ANY OTHER REASON.

Distributed exclusively by:

6901 South Pierce Street Suite 180
Littleton, CO 80128 USA

For the authorized fabricator nearest
to you, call 303-972-5107



**American Fiber
Cement Corporation**

